

## Caster Options

Hard surface, carpet and specialty casters





# WHY SHOULD I CHOOSE HARD FLOOR CASTERS?

New office chairs are typically equipped with hard caster wheels intended to be used on carpeted floor. But what if the chair ends up on a hard surface such as hardwood, VCT, ceramic tile, concrete, etc? Rolling the hard caster wheels on hard flooring can scratch or permanently damage your expensive hardwood, linoleum or tile floors. An additional benefit is a reduction in noise level in the workplace.

Solution? Replace the existing hard caster wheels with polyurethane caster wheels. The slightly softer polyurethane material will help prevent the wheels from scratching the hard floor while allowing the wheels to roll smoothly and quietly.

Besides cosmetic, safety is another reason why polyurethane caster wheels should be used on hard flooring. Polyurethane provides better traction on hard floor thus reducing the chance of accidental slipping.



#### HARD SURFACE CASTER



Premium hard floor caster. Hooded. 2" dia.

**CPS** Shroudless



Premium hard floor caster. Hooded. 2.5" dia. **CK** 



Casters lock while seated. 2" dia. CPLON



Weight release activates brake to prevent chair from moving when not in use. 2" dia. **CPL**<sup>OFF</sup>

ALL CASTERS ARE SOLD IN SETS OF 5 (FIVE).

NOTE:



#### **CARPET CASTER**



Standard hooded carpet caster. 2" dia.

CH CS Shroudless



Premium carpet caster. Hooded. 2.5" dia.

CH-60

### **SPECIALTY CASTERS**



Size: 2.5" diameter dual wheel

Material: Grey, non-marking Thermoplastic Elastomer

Capacity: 100 lbs per caster

Application: Medical

TP



Size: 2" diamete

**Material:** Grey, non-marking Neoprene, Chrome plated finish

**Capacity:** 125 lbs per caster **Application:** Medical

**Note:** Can be disassembled for cleaning

NP



Size: 3" diameter

Material: Grey, non-marking Polyurethane

"Dyna-Tred", Zinc finish

Capacity: 90 lbs per caster

**Application:** Extreme, factory, warehouse

Resistance: Resists chemicals, acids, caustic, and oils

Temperature: Range of -40°C to 82°C

**BXNL-E** 



Size: 3" diameter

Material: Grey, non-marking Monopreme,

Zinc finish

Capacity: 120 lbs per caster

**Application:** Medical

**BXNL-M** 





Size: 3" diameter

Material: Black, non-marking Polyolefin,

Zinc finish

Capacity: 120 lbs per caster

Application: Medical, factory, warehouse

BX With lock
BXNL Without lock



Size: 2.5" diameter

Material: Black, non-marking Neoprene,

Chrome plated finish 165 lbs per caster

**Capacity:** 165 lbs per a **Application:** Medical

**Note:** Can be disassembled for cleaning

Option: Total lock brake
NP25 Without lock
NP25L With lock





NSF: National Sanitation Foundation listed Material: Grey, non-marking rubber, Zinc finish

Capacity: 75 lbs per caster

**Application:** Food service, Sanitary environments **Note:** Can be disassembled for cleaning

NSF2 2" diameter NSF3 3" diameter

NOTE: ALL CASTERS ARE SOLD IN SETS OF 5 (FIVE).